

STREET/STRIP

PROCHARGER SUPERCHARGER SPECIFICATIONS



	A-1R	B-1	CS-1	C-1	C-2	P600B	P-1SC	P-1SC-1	P-1X	P-1R	D-1	D-1SC	D-1X	F-1D	F-1	F-1A	F-1A-91	F-1A-94
VOLUTE DIAMETER	7"	7"	7"	7"	7"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
MAX SUPERCHARGED HP	150	250	550	675	725	775	825	825	950	1250	925	925	1075	1050	1050	1100	1200	1300
MOTOR BASE HP RANGE*	50-95	60-150	150-325	150-325	175-375	200-500	200-500	200-450	300-500	300-500	300-500	300-500	300-550	300-500	300-500	300-500	300-500	300-550
MAX FLOW (CFM)	450	600	900	1,000	1,000	1,150	1,200	1,200	1,275	1,600	1,400	1,400	1,500	1,500	1,525	1,575	1,600	1,625
MAX BOOST (PSI)	15	20	24	24	24	24	30	32	32	36	32	32	32	34	38	38	38	38
INLET HOSE DIAMETER	3"	3"	3.5"	3.5"	3.5"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	4"
INDUCER DIAMETER	2.28"	2.28"	2.66"	2.75"	3.14"	3.37"	3.37"	3.37"	3.57"	3.75"	3.37"	3.37"	3.57"	3.37"	3.57"	3.5"	3.57"	3.7"
EXDUCER DIAMETER	3.2"	3.2"	3.7"	4.25"	4.25"	6.25"	6.25"	5.25"	5.56"	5.56"	6.25"	6.25"	6.20"	6.25"	6"	5.56"	5.56"	5.56"
OUTLET HOSE DIAMETER	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"
OUTLET I.D.	1.75"	1.75"	2.12"	2.12"	2.12"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"
MAX IMPELLER RPM	75,000	110,000	80,000	80,000	80,000	60,000	62,000	65,000	65,000	65,000	65,000	62,000	65,000	65,000	70,000	74,000	74,000	74,000
INTERNAL STEP-UP	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OIL CAPACITY	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz	4 oz	4 oz	4 oz	4 oz	4 oz

See Other Side for F-Series Supercharger Specs

913-338-2886 | SALES@PROCHARGER.COM | PROCHARGER.COM

10/25



MADE IN THE USA